

<b>Model</b>	<b>Unit</b>	<b>SJH 0432</b>	<b>SJH 0565</b>	<b>SJH 0676</b>	<b>SJH 06102</b>	<b>SJH 06120</b>	<b>SJH 0880</b>	<b>SJH 10150</b>	<b>SJH 10165</b>
Max. cut-off dia.	mm	Φ4	Φ5	Φ6	Φ6	Φ6	Φ8	Φ9	Φ9
Max. cut-off length	mm	32	65	76	102	120	82	150	165
RAM stroke	mm	58	92	124	158	158	140	220	220
Speed range	pcs /min	150-180	125-160	90-110	70-90	70-80	70-90	48-60	48-60
Main die size	mm	Φ30×45	Φ34.5×80.5	Φ45×100	Φ45×126	Φ45×146	Φ55×98	Φ65×168	Φ65×187
Rough punch size	mm	Φ24×58	Φ31×78	Φ36×103	Φ36×107	Φ36×107	Φ38×128	Φ48×150	Φ48×150
Fine punch size	mm	Φ20×54	Φ31×78	Φ36×103	Φ36×107	Φ36×107	Φ38×128	Φ40×150	Φ40×150
Cut-off-die size	mm	Φ15×30	Φ19×40	Φ25×40	Φ25×40	Φ25×40	Φ32×40	Φ32×44	Φ32×44
Cutter size	mm	8×30×62	9×32×65	10×35×76	10×38×83	10×38×83	14×40×96	14×50×100	14×50×100
Main motor	Kw	1.5	2.2	3.7	5.5	5.5	7.5	7.5	7.5
Oil pump	HP	1/4 (180W)	1/4 (180W)	1/4 (180W)	1/4 (180W)	1/4 (180W)	1/4 (180W)	1/2 (370W)	1/2 (370W)
Net weight	Kg	1000	1700	2500	2800	2800	3750	5150	5150
Machine dimensions	cm	160×109×126	190×110×145	280×120×135	307×125×135	307×125×135	307×125×135	440×160×160	440×160×160